

Compass R
High-Efficiency
Dry-Rotor Circulators
Impeller Assembly

Installation and
operating instructions

File No: 10.8975
Date: APRIL 22, 2019
Supersedes: NEW
Date: NEW

—

—


—

—

CONTENTS

1.0	Exploded assembly view	4
2.0	Replacement of impeller	5
3.0	Start-up	5
3.1	Before start- up	5
3.2	Venting the pump	5
4.0	Pump settings and pump performance	5
4.1	Pump performance curves	5

1.0 EXPLODED ASSEMBLY VIEW



INDEX	DESCRIPTION
1	Screw for controller housing M3×0.5×50
2	Screw gasket
3	Controller plate cover
4	Screw from controller housing to driver housing M3×0.5×12
5	Controller
6	ECM motor
7	Shaft key
8	Water slinger
9	Motor plate
10	Plate bolts / washers
11	O-ring
12	Mechanical seal
13	Impeller Impeller washer Impeller nut
16	Casing insert
17	Motor casing clasp
18	Casing

Compass R Replacement Motor

SR. NO	PART NUMBER	DESCRIPTION
1	819120-130	Impeller Assembly 20-75 and R25-140, R40-190

The Compass R impeller kit includes a impeller and an o-ring

NOTE:

Repair part numbers can be found in the Circulator Parts List,
File# 6010.201 (not all parts shown here are available for sale, this is to
show an entire breakdown of the Compass R)

2.0 REPLACEMENT OF IMPELLER

- 1 Turn off the pump leaving it installed in the line
- 2 Ensure electrical power is disconnected and locked out
- 3 Close the water supply at the points closest to the pump's inlet and outlet
- 4 For safety, allow water to cool to 100°F (40°C) before draining the system. It is best to leave the drain valve open while working on the system
- 5 Place a pan under the pump to collect the drain water
- 6 Bleed the water pressure from the pump
- 7 While holding the plumbing system, loosen the V-Clamp
- 8 Remove the motor assembly straight out from the volute being careful of the attached impeller from the plumbing system
- 9 Remove Impeller retaining nut
- 10 Remove Impeller
- 11 Reinstall the new impeller and retaining nut
- 12 Replace original O-Ring with new O-Ring, apply O-Ring lubricant
- 13 Reinstall the casing and the V-camp

3.0 START-UP

3.1 BEFORE START- UP

Fill the system with liquid and properly vent the system before starting the pump. The required minimum inlet pressure in relation to liquid temperature must be available at the pump inlet.

3.2 VENTING THE PUMP

Even with system vented, air may be still be present in the pump. The air in the pump may cause noise but the noise should cease after a few minutes running.

The venting process can be shortened by setting the pump to run at max speed for a short period of time (60 seconds).

Once the pump is vented (the noise has ceased), set the pump mode according to the recommendations.

CAUTION




The pump must not run dry.

4.0 PUMP SETTINGS AND PUMP PERFORMANCE

4.1 PUMP PERFORMANCE CURVES

Compass R 20-75 performance curves—Auto, Fixed Head, Fixed Speed and Proportional Pressure Curves



Manual control options

Fixed head curve - I, II, III

Fixed speed curve - PC1, PC2, PC3, PC4

Proportional pressure curve - PP1, PP2, PP3

AUTO - ■

Auto mode
(Factory default)



TORONTO

23 BERTRAND AVENUE
TORONTO, ONTARIO
CANADA
M1L 2P3
+1 416 755 2291

BUFFALO

93 EAST AVENUE
NORTH TONAWANDA, NEW YORK
U.S.A.
14120-6594
+1 716 693 8813

BIRMINGHAM

HEYWOOD WHARF, MUCKLOW HILL
HALESOWEN, WEST MIDLANDS
UNITED KINGDOM
B62 8DJ
+44 (0) 8444 145 145

MANCHESTER

WOLVERTON STREET
MANCHESTER
UNITED KINGDOM
M11 2ET
+44 (0) 8444 145 145

BANGALORE

#59, FIRST FLOOR, 3RD MAIN
MARGOSA ROAD, MALLESWARAM
BANGALORE, INDIA
560 003
+91 (0) 80 4906 3555

SHANGHAI

UNIT 903, 888 NORTH SICHUAN RD
HONGKOU DISTRICT
SHANGHAI, CHINA
200085
+86 (0)21 5237 0909

SÃO PAULO

RUA JOSÉ SEMIÃO RODRIGUES AGOSTINHO,
1370 GALPÃO 6
EMBU DAS ARTES
SAO PAULO, BRAZIL
+55 11 4785 1330

ARMSTRONG FLUID TECHNOLOGY
ESTABLISHED 1934

ARMSTRONGFLUIDTECHNOLOGY.COM

**MAKING
ENERGY
MAKE
SENSE™**